



# AGIP DIESEL SUPER MULTIGRADE

AGIP DIESEL SUPER MULTIGRADE is a multigrade oil suitable for the lubrication of all kinds of diesel engines including supercharged models installed in cars, trucks, buses, earthmoving and pit-and-quarry equipment, as well as fixed plant such as generating sets, etc. it may also be used in gasoline engines.

## CHARACTERISTICS (Typical Figures)

### AGIP DIESEL SUPER MULTIGRADE

|                     |       |               |
|---------------------|-------|---------------|
| <b>SAE grade</b>    |       | <b>15W-40</b> |
| Viscosity at 40° C  | cSt   | 110           |
| Viscosity at 100° C | cSt   | 14,5          |
| Viscosity Index     | -     | 135           |
| Viscosity at -15° C | mPa.s | 3400          |
| Appearance          | -     | B & C         |
| Flash Point COC     | °C    | 220           |
| Density at 15° C    | kg/l  | 0,884         |

## PROPERTIES AND PERFORMANCE

- AGIP DIESEL SUPER MULTIGRADE's detergent-dispersant properties together with its high and lasting capacity to neutralise combustion acid, place this product at high quality level. It keeps pistons clean and maintains solid product of combustion in suspension until the next oil change, thereby preventing the formation of dangerous deposits in the sump.
- There is no cold starting problem with AGIP DIESEL SUPER MULTIGRADE.
- AGIP DIESEL SUPER MULTIGRADE has characteristics perfectly suitable for all types of diesel engines operating under wide range of temperature conditions. Seasonal oil changes are thus avoided and trucks can travel from one geographical and climatic zone to another, as occurs with international road transportation today, without trouble.
- These properties are ensured by a special combination of low-ash additives, fully meeting the standards issued by all manufacturers of four-stroke diesel engines.
- Its superior anti-rust properties ensure effective protection of all parts of the engine.
- Its anti-wear properties remain fully effective throughout the period of service thus keeping the engine in the best possible condition.
- These properties are ensured by a special combination of low-ash additives, fully meeting the standards issued by all manufacturers of four-stroke diesel engines.

## SPECIFICATIONS

- API Service CF-4 / SG
- CCMC G4, PD2, D4
- MB.227.1
- MIL-L-2104 E LEVEL
- MIL-L-46152 E LEVEL